



Size	L	H <sub>1</sub>	H	d <sub>0</sub>	Flange JIS 10K FF				Weight (kg)
					D	C	t	n-h	
15A	174	193	243	Rc 3/4	95	70	12	4-15	8.5
20A	204	193	243	Rc 3/4	100	75	14	4-15	9.6
25A	204	193	243	Rc 3/4	125	90	14	4-19	10.1
32A	222	213	282	Rc 1	135	100	16	4-19	15.6
40A	242	213	282	Rc 1	140	105	16	4-19	16.3
50A	246	260	342	Rc 1	155	120	16	4-19	24.7
65A	288	314	418	Rc 1	175	140	18	4-19	40.0
80A	335	361	484	Rc 1 1/4	185	150	18	8-19	54.0
100A	390	445	594	Rc 1 1/4	210	175	18	8-19	96.0

8	Rivet	Carbon Steel	打込みねじ	S15C	2
7	Name Plate	Stainless Steel	銘板	SUS304	1
6	Plug	Carbon Steel	プラグ	S45C	1
5	Bolt	Carbon Steel	六角穴付ボルト	SCM435	1set
4	Gasket	Non Asbestos	ガスケット	Non Asbestos	1
3	Nozzle	Cast Iron	ノズル	FC200	1
2	Receiver	Ductile Cast Iron	レシーバー	FCD450	1
1	Body	Ductile Cast Iron	本体	FCD450	1
No.	Name of Parts	Material	部品名	材質	Q.TY

Specification	
Fluid	
Press.	MPa
Temp.	

## TYPE DS-2 DRAIN SEPARATOR ドレンセパレーター

Approval	T. Nishiyama
Check	T. Shinjo
Drawing	T. Nagasaka
Drawing No.	Y-737-6505
Date	10 MAR. 2009

