



Model (型式)	Orifice Size (オリフィスサイズ)	Max. Differential Press. (最高作動圧力差)
TB-5-5.6	1/8 (3.2mm)	0.56 MPa
TB-5-8.7	7/64 (2.8mm)	0.87 MPa
TB-5-10	#38 (2.5mm)	1.0 MPa

17	Plug	Carbon Steel	プラグ	AISI 1008-1010	1
15	Name Plate	Stainless Steel	銘板	SUS304	1
14	Bolt	Carbon Steel	六角ボルト	ASTM B633 TYPE1	6
13	Gasket	Non-Asbestos	ガスケット	Non-Asbestos	1
12	Guide Pipe	Stainless Steel	パイプノック	SUS304	1
11	Valve Seat	Stainless Steel	弁座	ASTM A582 440F	1
10	Valve	Stainless Steel	弁体	ASTM A582 440F	1
9	Lever	Stainless Steel	レバー	ASTM A240 304	1
8	Bucket	Stainless Steel	バケット	ASTM A240 304	1
7	Pipe	Carbon Steel	入口案内管	ASTM A53	1
6	Strainer	Stainless Steel	ストレーナ	SUS304	1
5	Strainer Cap	Carbon Steel	ストレーナキャップ	ASTM A108 Gr1215	1
4	Gasket	Soft Steel or Iron	ガスケット	Soft Steel or Iron	1
3	Plug	Stainless Steel	プラグ	SUS316	1
2	Cover	Cast Iron	ふた	ASTM A48 Class 30	1
1	Body	Ductile Cast Iron	本体	FCD450	1
No.	Name of Parts	Material	部 品 名	材 質	Q. TY

Size	L	H ₁	H	A	Flange JIS 10K FF					③ Plug	①⑦ Plug	Weight (kg)
					d	D	C	t	n-h			
15A	175	98	177	95.2	15	95	70	16	4-15	NPT1/4	NPT3/8	4.5
20A	195	98	177	95.2	20	100	75	18	4-15	NPT1/4	NPT3/8	4.9
25A	215	98	177	95.2	25	125	90	18	4-19	NPT1/4	NPT3/8	6.2

Specification	
Fluid	
Press.	MPa
Temp.	℃

TYPE TB-5 STEAM TRAP スチームトラップ

Approval	H. IWAMOTO
Check	Y. AOYAMA
Drawing	M. YOSHIDA
Drawing No.	Y-596-2205-1A
Date	2 APR. 2012

